

Flexo Wrap FR




- Mil-202, VW-1, FR-1 Approved
- Economical & Easy to Install
- Cut & Abrasion Resistant
- Hook & Loop Closure For Easy and Repeatable Access
- Temp Range -75°C to 125°C
- Melt Temp 250°C


Easy On, Easy Off Access Will Not Support Combustion

Flame Retardant Flexo Wrap (FWF) provides the same hook and loop wire management flexibility as our standard Flexo Wrap along with the added safety feature of an organic flame inhibitor to provide an additional level of security.

FWF is a safe, economical solution for a wide range of cable management applications where moderate levels of flame protection are needed.



FLEXO WRAP is designed for quick and easy management of wire, cable and hose assemblies. Just separate the hook and loop fasteners along the edge of the material....



and slip the entire length of FW around or under your harness or component assembly. The wide expandability range allows FW to easily fit around...



odd-shaped connectors and gently constrict around the diameter of your wires. When the FW is in place, simply seal the hook and loop along the edges.



Nominal Size	Part #	Hook & Loop Width	Standard Spool Put-Ups		Available Colors	Lbs/100'
			Bulk Spool	Mini Spool		
1/2"	FWF0.50	1/4"	100'	20'	TB	1.3
3/4"	FWF0.75	5/8"	100'	15'	TB	1.8
1 1/4"	FWF1.25	5/8"	100'	12'	TB	2.3
2"	FWF2.00	5/8"	100'	10'	TB	3.2

800 323-5140
www.techflex.com

