

Flexo Stainless

Braided Stainless Steel. Pre-Rounded For Installation Ease

Nothing protects hoses from wear and blowout quite like real Stainless Steel braid. It looks great in any application and is as strong as, well, steel. But, custom hoses overbraided with stainless steel are expensive, selections are often limited and production and delivery times can be an issue.

Now, you can take any stock or custom hose, slip a length of Flexo Stainless over it, hide the cut ends under your clamps and have the same look and protection as custom overbraided hoses at a fraction of the cost.

Flexo Stainless cuts with shears or serrated scissors (pg. 42), is pre-rounded for easy, slip on installation and is available in diameters and expansion ranges to accommodate virtually any common hose or wire application.

- Virtually Indestructible 304 Stainless Steel
- Won't Discolor or Rust
- Easy to Install
- Cuts With Shears
- Resists Abrasion. Chemicals and UV













To prevent fraying when cutting any metal braid, slip the sleeving over the intended application to get an accurate measurement, wrap the area to be cut with a couple of turns of tape, mark the cut and remove the sleeving. Use shears or serrated scissors to cut through the tape and sleeving. Don't remove the tape until the sleeving is installed and you're ready to terminate the end.

Nominal Size	Part #	'		Standard Spool Put-Ups		Available Colors	Lbs/100'
		Min.	Max.	Bulk Spool	Mini Spool	Colors	
1/2"	SSN0.50	1/4"	5/8"	100′	25′	Silver	4
5/8"	SSN0.63	3/8"	3/4"	100′	25′	Silver	5.8
3/4"	SSN0.75	1/2"	1"	100′	25′	Silver	5.2
1 "	SSN1.00	3/4"	1 1/4"	100′	25′	Silver	10
1 1/4"	SSN1.25	1″	1 1/2"	100′	25′	Silver	11
1 3/4"	SSN1.75	1 1/2"	2 1/4"	100′	25′	Silver	12