



- **Indestructible 304 Stainless Steel**
- **Cuts with Shears or Serrated Scissors**
- **Improves Burst Strength of Hoses**
- **Won't Discolor or Rust**
- **High Melt Temperature 2,650°F/1,450°C**
- **Flexible and Resistant to Vibration**

Braided Stainless Steel, Pre-Rounded For Installation Ease

STAINLESS STEEL (SSN) braid looks great in any application and is as strong as steel. Now, you can take any stock or custom hose, slip a length of Flexo Stainless over it, hide the cut ends under your clamps and have the same look and protection as custom overbraided hoses at a fraction of the cost. Braided Stainless Steel sleeving is used in applications where constant movement and high temperatures require a flexible, indestructible covering. Extremely high melt temperature makes this a great sleeving for automotive applications. Superior abrasion, chemical, and UV resistance make it great for outdoor applications.



Stainless Steel sleeving is used in applications such as expansion joints, where constant movement and high temperatures require a flexible, indestructible covering.



Contact your account representative for additional size information.

Nominal Size	Part #	Wall Thickness	Expansion Range		Standard Spool Put-Ups		Available Colors	Lbs/ 100'
			Min.	Max.	Bulk Spool	Shop Spool		
1/2"	SSN0.50SV	.025"	1/4"	5/8"	100'	25'	Silver (SV)	4.00
5/8"	SSN0.63SV	.025"	3/8"	3/4"	100'	25'	Silver (SV)	5.00
3/4"	SSN0.75SV	.025"	1/2"	1"	100'	25'	Silver (SV)	5.00
1"	SSN1.00SV	.025"	3/4"	1 1/4"	100'	25'	Silver (SV)	11.00
1 1/4"	SSN1.25SV	.035"	1"	1 1/2"	100'	25'	Silver (SV)	19.00
1 3/4"	SSN1.75SV	.040"	1 1/2"	2 1/4"	100'	25'	Silver (SV)	31.00

