


- **Resin Saturated, Heavy Weight Braided Fiberglass Won't Burn, Melt, or Become Brittle**
- **Minimal Dusting When Cut & Handled**
- **Cut and Abrasion Resistant**
- **Easy to Install - Cuts with Scissors**
- **Resists Gasoline and Engine Chemicals**

Resin Saturated Fiberglass Protects Up To 1,200°F

INSULTHERM (FGN) is an extremely high temperature resistant sleeve commonly used as thermal protection for wires, cables, and hoses that are subjected to continuous and extreme high temperature environments, such as engine manifolds and exhaust systems.

Insultherm is braided from fiberglass yarns and saturated with high temperature resins. FGN is tough and durable, maintaining its tight structure under extreme vibration, abrasion, mechanical stress, and temperature variations.



FGN is available in a wide range of diameters. It installs easily over a variety of applications to either deflect or retain heat in environments up to 1,200°F.



Insultherm resin saturated braided fiberglass sleeving is ideal in areas where fire and extremely high temperatures create a hazard to personnel and equipment.



Hoses insulated with Insultherm can perform better in the demanding environments where multi terrain equipment is used.



Nominal Size	Part #	Maximum Diameter	Wall Thickness	Standard Spool Put-Ups		Available Colors	Lbs/100'
				Bulk Spool	Shop Spool		
1/4"	FGN0.25	3/8"	.031"	200'	50'	SV & BK	2.00
3/8"	FGN0.38	5/8"	.043"	200'	50'	SV & BK	3.30
1/2"	FGN0.50	3/4"	.046"	200'	50'	SV & BK	4.80
5/8"	FGN0.63	7/8"	.046"	200'	50'	SV & BK	5.30
3/4"	FGN0.75	1 1/8"	.046"	200'	50'	SV & BK	6.40
7/8"	FGN0.88	1 1/4"	.046"	200'	50'	SV & BK	8.70
1"	FGN1.00	1 5/8"	.057"	100'	25'	SV & BK	10.50
1 1/2"	FGN1.50	2 5/8"	.061"	100'	25'	SV & BK	16.00
2 1/2"	FGN2.50	4 1/8"	.071"	100'	25'	SV & BK	19.70