

EASIEST, FASTEST INSTALL, NO DRILLING

Patent Pending

## MAGNETIC J HOOK MAGNETIC BRIDLE RING

## **Features:**

- Top Performing J Hooks and Bridle Rings
  - UL listed static load rating 17 lbs.
- World's Strongest Magnet's

## **Benefits:**

- 360 Degree Rotation
- Ability to Hang from Ground
- Labor/Time Savings
- Safer Working





C UL US

**31TS** 

Capacity:

3/4" J Hook 10 Cat 6 Cable
 15/16" J Hook 32 Cat 6 Cable
 2" J Hook 50 Cat 6 Cable

## Strength of 1/4-20 magnets on steel surface for part #'s:

- JH12MT, JH12MS, JH21MT, JH21MS, JH32MT, JH32Ms
- BRM4T125, BRM4T200
- MAG4TF

Vertical Pull Test		
Metal Thickness	Weight	
1 mm (.04 inch)	22 lbs	
2 mm (.08 inch)	45 lbs	
3 mm (.12 inch)	90 lbs	

Picture	Part #	Description
T P	JH12MT	¾" J Hook Magnet on Top
	JH21MT	1 5/16" J Hook Magnet on Top
	JH32MT	2" J Hook Magnet on Top
A A		·
	JH12MS	¾" J Hook Magnet on Side
	JH21MS	1 5/16 <sup>"</sup> J Hook Magnet on Side
	JH32MS	2" J Hook Magnet on Side
	BRM2T75	¾" Magnetic Bridle Ring 10-24
	BRM4T125	1 ¼" Magnetic Bridle Ring ¼-20
	BRM4T200	2" Magnetic Bridle Ring ¼-20
9	62452	10 lb Hook and Loop Holder -Black
	62455	5 lb Std. Cable Tie Mount –Black
	62406	10 lb Std. Cable Tie Mount –White
	62411	10 lb Std. Cable Tie Mount –Black
	62416	15 lb Std. Cable Tie Mount –White
	62417	15 lb Std. Cable Tie Mount -Black
0	62401	½" Magnetic Cable Holder –White
	62409	½" Magnetic Cable Holder –Black
	62413	¾" Magnetic Cable Holder –White
	62419	¾" Magnetic Cable Holder –Black
6	62415	1" Magnetic Cable Holder –White
	62421	1" Magnetic Cable Holder –Black
	62450	½" Magnetic Clamp
-X	MAG4TF	1/4-20 Magnet w/ Female Standoff
	MM100	4 Mount Magnet w/ Hardware Only
(9)		
	62400	Cable Hanning Tabl
	62499	Cable Hanging Tool
		as now assessed any liability for damages resulting from

Please read before us. Disclaimer: Mag-Daddy neither assumes nor accepts any liability for damages resulting from the handling or use of magnets. With your purchase, the buyer confirms that you have read and understood the following warnings: the buyer agrees that he/she is responsible for all damages and injuries caused by the magnets, which include personal injuries, property damages and magnet damages. The buyer must agree with the terms before purchase. Pull forces we have provided are estimates only, we are not responsible for any inaccuracy of the magnet pull force. Please test the pull force before any usage.

Magnets are very strong. Handling them with care is necessary to prevent personal injuries, property damages and magnet damages. Can be harmful to pacemaker wearers and others with medical implants.